

# New!

## White LEDs in Emergency Battery Units and Remotes

Product	Features	Replacement Lamps		
		Ordering Code	Type	Volts/Watts
 <p><b>EF40 Series</b> Remote Fixture</p> <ul style="list-style-type: none"> <li>Quality illumination requires fewer fixtures</li> <li>Shielded to prevent tampering</li> <li>Easy installation</li> <li>Easy Lamp replacement</li> </ul>		580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E		24V - 20W
		580.0093-E	LED	12V - 4W
 <p><b>Literay Series</b> Wall Mount Remote Head</p> <ul style="list-style-type: none"> <li>Compact wall sconce unit for indoor and outdoor use</li> <li>High impact resistant polycarbonate diffuser</li> <li>Corrosive resistant die-cast aluminum housing</li> <li>Vandal resistant</li> </ul>		570.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E		24V - 20W
		580.0093-E	LED	12V - 4W
 <p><b>EF9/EF9Q/EF9M Series</b> Micro Tungsten Quartz and MR16 Lamps</p> <ul style="list-style-type: none"> <li>Variable light patterns using adjustable lens</li> <li>Fire-retardant thermoplastic</li> <li>300° rotation</li> </ul>		570.0016-E	Tungsten	6V - 9W
		570.0045-E	Tungsten	24V - 9W
		580.0015-E	Halogen (quartz)	12V - 12W
		580.0093-E	LED	12V - 4W
 <p><b>Distinction Series</b> Surface Designer Series</p> <ul style="list-style-type: none"> <li>Remote head: 1, 2 or 3 head configurations</li> <li>Highly-resistant powder-coated, die cast aluminum construction</li> <li>6W, 10W, 12W, 20W, 35W, and 50W availability</li> </ul>		570.0074-E	MR16-Flood	6V - 6W
		580.0080-E		12V - 12W
		580.0077-E		24V - 20W
		580.0093-E	LED	12V - 4W
 <p><b>EFR Distinction</b> Remote Collection Recessed Designer Series</p> <ul style="list-style-type: none"> <li>6W, 10W, 12W, 20W, 35W, and 50W availability</li> <li>Choice of housing for new construction or insulated ceiling</li> <li>EFR8NB and EFR8R are made of powder coated or electro-plated steel</li> <li>EFR9 is made of die-cast</li> </ul>		580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E		24V - 20W
		580.0093-E	LED	12V - 4W
 <p><b>Survive-All EF39 Series</b> NEMA-4X Certified Remote Fixture</p> <ul style="list-style-type: none"> <li>Fully gasketed cast aluminum back plate with clear polycarbonate cover – NEMA-4X Certified</li> <li>UV and impact resistant cover, choice of single or double lamp models</li> <li>Available in 6, 12 and 24 volts models with various wattages</li> <li>NSF Certified for food processing plants**</li> </ul>		580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E		24V - 12W
		580.0093-E	LED	12V - 4W
 <p><b>Retract-a-Lite Series</b></p> <ul style="list-style-type: none"> <li>Remote only visible upon power failure</li> <li>Front can be painted or wall papered on-site to match existing decor</li> </ul>		580.0080-E, 580.0064-E 580.0083-E, 580.0076-E	MR16 flood	12V-12W-50W
		580.0068-E, 580.0090-E 580.0089-E	MR16 High-output	12V-20W-50W
		580.0093-E*	LED	12V - 4W
 <p><b>Mini Retract-a-Lite</b> Fully Concealed, Easy to Retrofit</p> <ul style="list-style-type: none"> <li>Easy to retrofit in finished walls: the unit slides in through an 8.25-in by 5.75-in hole, open next to a wall stud, no pre-installed back box</li> <li>Output: 12Vdc with up to 100 watts of power</li> <li>Direct connection to 120 or 347Vac power generators</li> </ul>		580.0080-E, 580.0064-E 580.0083-E, 580.0076-E	MR16 flood	12V-12W-50W
		580.0068-E, 580.0090-E 580.0089-E	MR16 High-output	12V-20W-50W
		580.0093-E*	LED	12V - 4W
 <p><b>Distinction Series</b> 6, 12 and 24 Volts Decorative Battery Units</p> <ul style="list-style-type: none"> <li>Rugged steel cabinet with corrosion-resistant undercoating</li> <li>Solid-state pulse-type charger – current-limited, temperature-compensated, short-circuit proof and reverse-polarity protected.</li> <li>Electronic lockout and brownout circuits</li> <li>Long-life, maintenance-free lead acid battery, NEXUS® compatible**</li> </ul>		580.0074-E	MR16 - Flood	6V-6W
		580.0079-E		6V-10W
		580.0093-E	LED	12V - 4W
 <p><b>JMLA Series</b> 6 and 12 Volts Decorative Battery Units</p> <ul style="list-style-type: none"> <li>Rugged steel cabinet with corrosion-resistant undercoating</li> <li>Solid-state pulse-type charger – current-limited, temperature-compensated, short-circuit proof and reverse-polarity protected</li> <li>Unit comes standard with electronic lockout and brownout circuits</li> <li>Long-life, maintenance-free lead acid battery, NEXUS® compatible**</li> </ul>		580.0074-E	MR16	6V - 6W
		580.0079-E		6V - 10W
		580.0080-E		12V - 12W
		580.0068-E	12V - 20W	
580.0093-E	LED	12V - 4W		
 <p><b>Survive-All NXM Series</b> NEMA-4X Certified Battery Unit</p> <ul style="list-style-type: none"> <li>Fully gasketed cast aluminum back plate with clear polycarbonate cover – NEMA-4X Certified</li> <li>NSF Certified for food processing plants, cold weather option (-40°C)</li> <li>Comes standard with non-audible advanced diagnostic charger board, 10 minute time delay and lamp disconnect</li> <li>Long-life, maintenance free sealed lead acid battery**</li> </ul>		580.0074-E	M6W, MR16, 6V - 6W, flood	
		580.0079-E	M10W, MR16, 6V - 10W, flood	
		580.0080-E	M12W, MR16, 12V - 12W, flood	
		580.0068-E	MH20W, MR16, 12V - 20W	
		580.0093-E	LED, 12V - 4W	

\*Please consult the Emergi-Lite product catalogue or website for precise lamp ordering information

\*\*For more extensive product information please consult the Emergi-Lite product catalogue or website

Continued on next page ➔





**New!**

## White LEDs in Emergency Battery Units and Remotes

### Hazardous Location Series

- Certified Class I Zone 2, Groups IIA, IIB and IIC
- Certified Class I Division 2, Groups A, B, C and D as per CSA C22.2 No.137-M1981

Product	Features	Replacement Lamps		
		Ordering Code	Type	Volts/Watts
 <p><b>EXHZ Series</b> Combination Unit for Hazardous Locations</p>	<ul style="list-style-type: none"> <li>● Certified Class I Zone 2, Groups IIA, IIB and IIC</li> <li>● Certified Class I Division 2, Groups A, B, C and D as per CSA C22.2 No.137-M1981</li> <li>● Polymeric frame, with built-in gasket to prevent water infiltration</li> <li>● Heavy-duty 1/8-inch thick aluminum back plate with key-holes for secure wall-mount installation</li> <li>● Two MR16 halogen lamps, shielded by a cast aluminum housing and a polycarbonate cover</li> <li>● Sealed, maintenance-free, Lead-Calcium or Nickel-Cadmium batteries</li> <li>● Remote load capacity</li> </ul>	580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E	24V - 12W	
		580.0093-E	LED	12V - 4W
 <p><b>HZM Series</b> Battery Unit for Hazardous Locations</p>	<ul style="list-style-type: none"> <li>● Certified Class I Zone 2, Groups IIA, IIB and IIC</li> <li>● Certified Class I Division 2, Groups A, B, C and D as per CSA C22.2 No.137-M1981</li> <li>● Suited for areas with the risk of flammable gases, vapors or liquids that can create an explosive atmosphere</li> <li>● Two MR16 halogen or LED lamps, shielded by a cast Aluminum housing and a polycarbonate cover</li> <li>● Sealed, maintenance-free, Lead-Calcium batteries with up to 120W emergency power</li> </ul>	580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E	24V - 12W	
		580.0093-E	LED	12V - 4W
 <p><b>EF41 Series</b> Remote Fixture for Hazardous Locations</p>	<ul style="list-style-type: none"> <li>● Certified Class I Zone 2, Groups IIA, IIB and IIC</li> <li>● Certified Class I Division 2, Groups A, B, C and D as per CSA C22.2 No.137-M1981</li> <li>● Extreme operational temperature range: -40°C to +40°C.</li> <li>● Input voltage: 6V, 12V, 24V or 120V</li> <li>● Fully gasketed die-cast aluminum back plate</li> </ul>	580.0079-E	MR16-Flood	6V - 10W
		580.0080-E		12V - 12W
		580.0077-E	24V - 12W	
		580.0093-E	LED	12V - 4W

Please consult the Emergi-Lite product catalogue or website for precise lamp ordering information  
For more extensive product information please consult the Emergi-Lite product catalogue or website