


Resi-Gard


Nonmetallic adapters and couplings

For use with Riser-Gard and general purpose


Couplings

	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA240E	3/4	Orange	25	0.783
	SCA240F	1	Orange	20	0.972

Threaded adapters


	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA243E	3/4	Orange	100	2.30
	SCA243F	1	Orange	50	2.00

Snap-in adapters


	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA253E	3/4	Orange	100	2.90
	SCA253F	1	Orange	50	2.30

For use with Plenum-Gard


Coupling

	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	A340F	1	Orange	50	2.50

Threaded adapter

	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	A343F	1	Orange	50	1.55

Snap-in adapter

	Cat. no.	Size (in.)	Colour	Std. ctn. qty.	Std. ctn. wt. (lb)
	A353F	1	Orange	50	3.00

Resi-Gard

Flexible raceway (approved for low voltage use only)




Standard length reels

Cat. no.	Size (in.)	Pull tape length (ft.)	Reel length (ft.)	Prod. wt. (lb)
SCE4X1-1000	¾	Empty	1,000	115.0
SCF4X1C-1500	1	900 lb	1,500	268.5
SCJ4X1C-500	2	900 lb	500	133.5


Resi-Gard fittings

A complete line of Carlon one-piece quick connect couplings, threaded adapters and snap-in terminator adapters are available for quick, easy professional installation of Resi-Gard flexible raceway.

Quick connect couplings

	Cat. no.	Size (in.)	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA240E	¾	25	0.783
	SCA240F	1	20	0.972

Quick connect threaded adapters


	Cat. no.	Size (in.)	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA243E	¾	25	0.633
	SCA243F	1	20	0.778

Ideal for providing a main chase from the main distribution panel to a secondary hub in the attic or basement. Resi-Gard nonmetallic flexible raceway is available in ¾ in. to 2 in. diameter sizes with factory installed pull tape in sizes 1 in. to 2 in. The raceway is hand bendable, lightweight and easily cut to length to reduce scrap. Bright orange colour clearly signifies a low voltage installation.


Standard length coils

Cat. no.	Size (in.)	Pull tape length (ft.)	Coil length (ft.)	Prod. wt. (lb)
SCE4X1-100	¾	Empty	100	11.5
SCF4X1C-100	1	900 lb	100	17.9
SCG4X1C-100	1¼	900 lb	100	21.5
SCH4X1C-50	1½	900 lb	50	11.2
SCJ4X1C-50	2	900 lb	50	13.4


Quick connect snap-in adapters

	Cat. no.	Size (in.)	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCA253E	¾	25	0.783
	SCA253F	1	20	0.918

Male terminal adapters*

	Cat. no.	Size (in.)	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCE943G	1¼	50	3.0
	SCE943H	1½	25	2.5
	SCE943J	2	50	6.8

Standard couplings*

	Cat. no.	Size (in.)	Std. ctn. qty.	Std. ctn. wt. (lb)
	SCE940G	1¼	30	3.5
	SCE940H	1½	25	3.9
	SCE940J	2	30	5.2

*Must be cemented to Resi-Gard flexible raceway using only Resi-Gard solvent cement.